

nginx reverse proxy configuration

/etc/nginx/sites-available/meet.shiny.space

(why debian?? we don't need sites-available for nginx... switch to alpine sometime)

```
server {
    listen 443 ssl;

    server_name meet.shiny.space;
    client_max_body_size 500M;
    location /.well-known {
        root /var/www/html;
        try_files $uri $uri/ = 404;
    }
    location /xmpp-websocket {
        proxy_pass http://10.0.0.30:8000;
        proxy_http_version 1.1;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection "upgrade";
    }
    location /colibri-ws {
        proxy_pass http://10.0.0.30:8000;
        proxy_http_version 1.1;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection "upgrade";
    }
    location /http-bind {
        proxy_pass http://10.0.0.30:8000;
        proxy_http_version 1.1;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection "upgrade";
    }
    location / {
```

```
proxy_pass http://10.0.0.30:8000;  
}  
}
```

Revision #3

Created 2024-10-09 23:58:21 UTC by Admin

Updated 2025-03-06 14:56:32 UTC by Admin